

I claim:

- Sub 101
1. An eaves trough support bracket comprising:
- (a) a main beam having longitudinally spaced distal and proximal ends, laterally spaced first and second edges, and transversely spaced first and second surfaces;
 - (b) a connection element extending in a first transverse direction from the distal end of the main beam;
 - (c) a hook extending in the first transverse direction and a second longitudinal direction from the proximal end of the main beam, and defining a concavity open in a second transverse direction;
 - (d) a first leg extending in a second transverse direction from the first edge of the main beam with a proximal longitudinal end substantially transversely aligned with the proximal end of the main beam; and
 - (e) a second leg extending in the second transverse direction from the second edge of the main beam with a proximal longitudinal end substantially transversely aligned with ~~the proximal end of the main beam.~~
2. The bracket of claim 1 wherein the bracket is configured and arranged such that the bracket can be formed from a unitary planar metal blank.
3. The bracket of claim 1 comprising a laterally extending first bend line along a transition line from the main beam to the connection element.
4. The bracket of claim 3 further comprising at least one rib formed within the main beam and the connection element which extends across and substantially perpendicular to the first bend line, whereby the longitudinal structural strength of the bracket along the first bend line is improved.
5. The bracket of claim 1 comprising a laterally extending second bend line along a transition line from the main beam to the hook.
6. The bracket of claim 5 further comprising at least one rib formed within the main beam and the hook which extends across and substantially perpendicular to the second bend line, whereby the longitudinal structural strength of the bracket along the second bend line is improved.

7. The bracket of claim 1 wherein the connection element includes (i) a strut with a first transverse end connected to the distal end of the main beam and a second transverse end extending in a first transverse direction from the distal end of the main beam, and (ii) a tab with a first longitudinal end connected to the second transverse end of the strut and a second transverse end extending in a second longitudinal direction from the second transverse end of the strut.

8. The bracket of claim 7 comprising a laterally extending third bend line along a transition line from the strut to the tab.

9. The bracket of claim 8 further comprising at least one rib formed within the strut and the tab which extends across and substantially perpendicular to the third bend line, whereby the longitudinal structural strength of the bracket along the third bend line is improved.

10. The bracket of claim 1 wherein the hook includes (i) a transversely extending shaft portion with a first end connected to the proximal end of the main beam and a second end extending in the first transverse direction from the proximal end of the main beam, (ii) a hooking portion with a first end connected to the second end of the shaft and a second end extending away from the distal end of the main beam in a second longitudinal direction from the second end of the shaft, and (iii) a transversely extending extension portion with a first end connected to the second end of the hooking portion and a second end extending in the second transverse direction from the second end of the hooking portion.

11. The bracket of claim 1 further comprising a longitudinally extending fourth bend line along a transition line from the main beam to the first leg.

12. The bracket of claim 11 further comprising a longitudinally extending fifth bend line along a transition line from the main beam to the second leg.

13. The bracket of claim 1 further comprising a longitudinally aligned hole through each of the shaft and extension portions of the hook effective for accommodating partial passage of a mechanical fastener throughout the holes.

14. The bracket of claim 1 wherein the proximal longitudinal ends of the first and second legs independently have a transverse height of about 0.5 to 1.5 inches.

15. The bracket of claim 12 wherein (i) the fourth and fifth bend lines each have a distal longitudinal end proximate the distal end of the main beam, and (ii) at least one rib which extends across and is substantially perpendicular to the first bend line extends beyond the distal longitudinal ends of the fourth and fifth bend lines in the second transverse direction.

16. The bracket of claim 1 wherein the bracket is formed from a single unitary piece of metal.

17. The bracket of claim 16 wherein the metal is aluminum.

18. An article of commerce, comprising:

- (a) a length of eaves trough; and
- (b) a plurality of eaves trough support brackets comprising:
 - (i) a main beam having longitudinally spaced distal and proximal ends, laterally spaced first and second edges, and transversely spaced first and second surfaces,
 - (ii) a connection element extending in a first transverse direction from the distal end of the main beam,
 - (iii) a hook extending in the first transverse direction and a second longitudinal direction from the proximal end of the main beam, and defining a concavity open in a second transverse direction,
 - (iv) a first leg extending in a second transverse direction from the first edge of the main beam with a proximal longitudinal end substantially transversely aligned with the proximal end of the main beam, and
 - (v) a second leg extending in the second transverse direction from the second edge of the main beam with a proximal longitudinal end substantially transversely aligned with the proximal end of the main beam.

19. A method of installing eaves trough, comprising the steps of:

- (a) obtaining a length of eaves trough defining a water diversion channel and comprising:
 - (i) a bottom having longitudinally spaced and laterally extending first and second edges,
 - (ii) a back wall transversely extending from the second laterally extending edge of the bottom and having a laterally extending distal edge ~~transversely spaced from the bottom in a primary transverse direction,~~



- add a_3